

Warranty

24
Months



Pin Vice: Tension, Fracture, Insert/ Withdraw Force Measurement, 2 pieces
AC 01, net



Cable fixture, Tension & Fracture, all kinds of cables up to 5 kN, 2 pieces
AC 10, net



Ball shaped Head: Test tensile & Pressure strength, up to 5 kN, 3 pieces
AC 02, net



Rolling-clamp, Tension, Fracture Force up to 5 kN, 2 pieces
AC 11, net



Thin Film Grip: Tension, fracture, Insert/ Withdraw up to 5 kN, 2 pieces)
AC 03, net



1-jaw-clamp, tension, peeling Force measurement up to 5 kN, 2 pieces
AC 13, net



Wedge grip for tensile tests for heavy duty use up to 5 kN, 1 piece
AC 04 (up to 5 kN), net
AC 37 (up to 10 kN), net



Ring-Fixture, tension and fracture measurement up to 500 N, 2 pieces
AC 15, net



Parallel jaw grip push or pull tests up to 5 kN, 2 pieces
AC 12, net



Heavy-duty-clamp, push and pull tests up to 5 kN, 2 pieces
AC 16, net



Fine point clamp, push or pull tests up to 500 N, width: 15 mm, 2 pieces
AC 14, net



Long clamp, light clamp specialised in **Low-load tests** up to 50 N, 2 pieces
AC 17, net



Wheel attachment up to 200 kN, tensile test of components e.g. cable & plug, 1 Set
AC 07, net



2-jaw-grip, tension & fracture tests up to 5 kN, 2 pieces
AC 18, net



Pressure Disc, Compression & Fracture Measurement up to 5 kN, \varnothing 49 mm, 2 pieces
AC 08, net



Cylinder Top, Test tensile strength of springs up to 5 kN, 2 pieces
AC 19 net



Grip Clamp, tension measurement up to 5 kN, 2 pieces
AC 09, net



„Tuning Forc“ (joint device such as the keyboard carrier), up to 5 kN, 1 piece
AC 20, net



Metal plate for FH external Sensor up to 5 kN, 85 mm diameter, 2 pieces
AFH 06, net



Heavy-duty-grip for Pulltests, 1 piece
AC 31 (up to 5 kN), net
AC 32 (up to 10 kN), net



Broad clamp with quick opening device width: 30 mm, up to 500 N, 2 pieces
AC 22, net



Low profile clamp for Pulltests up to 500 N, esp. for Wheel balancing. 1 piece
AC 33, net



Stainless steel **handle bar** with rubber grip for FH remote sensor, 1 piece
AFH 05, net



Stainless steel **handle bar** with rubber grip for safe handling, 1 piece for
FA, FH, AFH 04 net
FT, **AFT 02** net
FK, **AFK 02** net